

**Town of Bethlehem  
Selectmen's Office  
36 Main Street South \* PO Box 160  
Bethlehem, CT 06751-0160  
(203)266-7510 \* fax (203)266-7670**


**Invitation to Bid**

**Memorial Hall Door Replacement**

Sealed bids to replace four exterior doors at Memorial Hall will be received at the Selectmen's Office until 11:00AM Friday July 12, 2019 at which point they will be opened and read. Bid forms and specifications are available at the Selectmen's Office Tuesday-Friday 9:00AM – Noon. The award may be made at a later date. The Town reserves the right to reject any and all bids and to award the bid deemed to be in the best interest of the Town.

Appointments to visit the site can be made by contacting Mr. Bruce Hoffman, committee member at 203-266-7355.

Very Truly Yours,



**Leonard Assard  
First Selectman**

**Town of Bethlehem  
Bid Form  
Memorial Hall Door Replacement**

The undersigned proposes to furnish and install four exterior doors in conformance with the specifications for the prices listed below.

Opening 1 Kitchen Door

Written words

Numerals

Opening 2 South Side  
Double Door

Written words

Numerals

Opening 3 Rear Double Door

Written words

Numerals

Opening 4 Front Entrance

Written Words

Numerals

Signed

Company

Date

Estimated completion date

Bid specifications for Bethlehem Memorial Hall door and hardware replacements.

Contractor will supply all Materials, Labor, Tools and Equipment required to install new Frame, Doors, and Hardware as follows:

#### OPENING #1 - Kitchen door

Door: CECO Imperial 3068 18GA. Galvanized, insulated, 9 lite with 2 embossed

panels.

Glass: 1/2" clear, tempered, insulated with white 9 lite grid inside glass.

Lock: Corbin Russwin ED5200 X N955 trim, exit device. Cylinder by owner.

Hinges: McKinney TA2714 4 1/2" x 4 1/2" NRP Hinges 26D.

Closer: Corbin Russwin DC6210 with HD A5 hold open arm with stop.

Perimeter weather stripping: Pemko 303APK

Door sweep: Pemko 307AV

Existing frame and threshold to remain.

#### INSTALLATION:

Remove existing door and hardware.

Secure frame as required to provide a solid attachment and re-caulk opening with

One part urethane caulking. Sika Sikaflex 1A one part polyurethane caulk or

equal.

Install hardware per manufacturer's instructions.

Remove all debris from site.

#### OPENING #2 - South side pair of doors

Doors: CECO Imperial 3068 18GA. Galvanized, insulated, 9 lite, 2 panel

embossed doors.

Glass: 1/2" clear tempered, insulated with 9 lite grid inside glass.

Lock: Active - Corbin Russwin surface vertical rod ED5800 X N955 trim, exit

device. Cylinder by owner.

Lock: Inactive - Corbin Russwin surface vertical rod ED5800 exit only, exit

device.

Hinges: Select S154 HD half surface continuous hinges.

Closers: 2- Corbin Russwin DC6210 with HD A5 hold open arm with stop.

Perimeter weather stripping: Pemko 303APK

Meeting stile weather stripping: Pemko 29324 CNB with black brush.

Door sweep: Pemko 307AV.

Existing frame and threshold to remain.

#### INSTALLATION

Remove existing doors and hardware.

Secure frame as required to provide a solid attachment and re-caulk opening

with Sika Sikaflex 1A one part, polyurethane caulk or equal.

Install hardware per manufacturer's instructions.

Remove all debris from site.

OPENING #3 - Rear Entrance pair of Doors  
Doors: CECO Imperial 3068 18GA. Galvanized, insulated, flush doors.  
Lock: Active - Corbin Russwin surface vertical rod ED5800 X N955 trim, exit device. Cylinder by owner.  
Lock: Inactive - Corbin Russwin surface vertical rod ED5800 exit only, exit device.  
Hinges: Select SL54 HD half surface continuous hinges.  
Closers: 2 - Corbin Russwin DC6210 with HD A5 hold open arm with stop.  
Perimeter weather stripping: Pemko 303APK  
Meeting stile weather stripping: Pemko 29324 CNB with black brush.  
Door Sweep: Pemko 307AV  
Existing frame and threshold to remain.

## INSTALLATION

Remove existing doors and hardware.  
Secure frame as required to provide a solid attachment and re-caulk opening with one part Sikaflex 1A one part, polyurethane caulk or equal.  
Install hardware per manufacturer's instructions.  
Remove all debris from site.



#### OPENING #4 - Front Entrance

Doors: Complete new unit consisting of : Two 3'0" x 7'0" Cleary Captiva Traditional doors #8369 sapele mahogany, ovoio sticking, bevel panel, with #8706 side lite panels with 1-3/8" mutins and ADA compliant aluminum sill. Unit mounted in a 5/4" framesaver jamb.

Lock: Active - Corbin Russwin surface vertical rod ED5800 X N955 trim, exit device satin brass finish. Cylinder by owner.  
Lock: Inactive - Corbin Russwin surface vertical rod ED5800 exit only, exit device satin brass finish.

Closers: 2 - Corbin Russwin DC6210 with HD A5 hold open arm with stop. 606 Meeting stile weather stripping: Pemko 29324 CNG with black brush.  
Door Sweep: Pemko 315 GN  
6 1/4" x 34" kick plates 606.

Exterior PVC trim to match existing, 5/4 x 8 fluted pilasters with plinth blocks, 5/4 x 10 head trim with 1 - 3/4" bed molding with cap and 2-3/4" crown molding with 3/4" cap. Interior trim to match existing stained pine.

#### INSTALLATION

Remove existing doors, sidelites and trim.  
Install new unit with exterior and interior trim and threshold.  
Install hardware per manufacturer's instructions.  
Repair and grout floor tile as needed to meet ADA guidelines.  
Remove all debris form site.

**SUBSTITUTIONS:** Products listed are the basis of design. Any substitution for an equal shall be noted in the bid and product data provided for evaluation. If substitutions are rejected, the bidder will provide the basis of design products.