

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
1.	AMERICAN ELECTRIC	11510SCA480R2FGNREC	LUMINAIRE - COBRA HEAD - 100 WATT HPS, 480 VOLT, MCII	EA	
2.	AMERICAN ELECTRIC	11515SCA480R2DGNREC	LUMINAIRE - COBRA HEAD - 150 WATT HPS, 480 VOLT, MSII	EA	
3.	AMERICAN ELECTRIC	11515SCAMT2R2DGNREC	LUMINAIRE - COBRA HEAD - 150 WATT HPS, MULTI-VOLT, MSII	EA	
4.	AMERICAN ELECTRIC	11515SCA480R2FGNREC	LUMINAIRE - COBRA HEAD - 150 WATT HPS, 480 VOLT, MCII	EA	
5.	AMERICAN ELECTRIC	11515SCAMT2R2FGNREC	LUMINAIRE - COBRA HEAD - 150 WATT HPS, MULTI-VOLT, MCII	EA	
6.	AMERICAN ELECTRIC	11520SCA480R2DGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, 480 VOLT, MSII	EA	
7.	AMERICAN ELECTRIC	11520SCAMT2R2DGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, MULTI-VOLT, MSII	EA	
8.	AMERICAN ELECTRIC	11520SCA480R3DGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, 480 VOLT, MSIII	EA	
9.	AMERICAN ELECTRIC	11520SCAMT2R3DGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, MULTI-VOLT, MSIII	EA	
10	AMERICAN ELECTRIC	12520SCA480R2FGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, 480 VOLT, MCII	EA	
11	AMERICAN ELECTRIC	12520SCAMT2R2FGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, MULTI-VOLT, MCII	EA	
12	AMERICAN ELECTRIC	12520SCA480R3FGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, 480 VOLT, MCIII	EA	
13	AMERICAN ELECTRIC	12520SCAMT2R3FGNREC	LUMINAIRE - COBRA HEAD - 200 WATT HPS, MULTI-VOLT, MCIII	EA	
14	AMERICAN ELECTRIC	11525SCA480R2DGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, 480 VOLT, MSII	EA	
15	AMERICAN ELECTRIC	11525SCAMT2R2DGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, MULTI-VOLT, MSII	EA	
16	AMERICAN ELECTRIC	11525SCA480R3DGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, 480 VOLT, MSIII	EA	
17	AMERICAN ELECTRIC	11525SCAMT2R3DGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, MULTI-VOLT, MSIII	EA	
18	AMERICAN ELECTRIC	12525SCA480R2FGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, 480 VOLT, MCII	EA	
19	AMERICAN ELECTRIC	12525SCAMT2R2FGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, MULTI-VOLT, MCII	EA	
20	AMERICAN ELECTRIC	12525SCA480R3FGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, 480 VOLT, MCIII	EA	
21	AMERICAN ELECTRIC	12525SCAMT2R3FGNREC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, MULTI-VOLT, MCIII	EA	
22	AMERICAN ELECTRIC	12525SCAMT2R2FGECPC	LUMINAIRE - COBRA HEAD - 250 WATT HPS, MULTI-VOLT, MCII, WITH PE RECEPTACLE	EA	
23	AMERICAN ELECTRIC	12540SCA480R2DGNREC	LUMINAIRE - COBRA HEAD - 400 WATT HPS, 480 VOLT, MSII	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
24	AMERICAN ELECTRIC	12540SCA480R3DGNREC	LUMINAIRE - COBRA HEAD - 400 WATT HPS, 480 VOLT, MSIII	EA	
25	AMERICAN ELECTRIC	12540SCA480R2FGNREC	LUMINAIRE - COBRA HEAD - 400 WATT HPS, 480 VOLT, MCII	EA	
26	AMERICAN ELECTRIC	12540SCA480R3FGNREC	LUMINAIRE - COBRA HEAD - 400 WATT HPS, 480 VOLT, MCIII	EA	
27	AMERICAN ELECTRIC	12540SCAMT2R3FGNREC	LUMINAIRE - COBRA HEAD - 400 WATT HPS, MULTI-VOLT, MCIII	EA	
28	AMERICAN ELECTRIC	ATB0-30BLED10-480-R2-20-NL-NR	LED LUMINAIRE – COBRA HEAD, 105 WATT (APPROX.), 12,400 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
29	AMERICAN ELECTRIC	ATB0-30BLED10-480-R3-20-NL-NR	LED LUMINAIRE – COBRA HEAD, 105 WATT (APPROX.), 12,700 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
30	AMERICAN ELECTRIC	ATB0-30BLED10-MVOLT-R2-20-NL-NR	LED LUMINAIRE – COBRA HEAD, 105 WATT (APPROX.), 12,400 LUMEN (APPROX.), 4000K, MULTI-VOLT 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
31	AMERICAN ELECTRIC	ATB0-30BLED10-MVOLT-R3-20-NL-NR	LED LUMINAIRE – COBRA HEAD, 105 WATT (APPROX.), 12,700 LUMEN (APPROX.), 4000K, MULTI-VOLT 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
32	AMERICAN ELECTRIC	ATB0-30BLED10-MVOLT-R3-20-NL-PCLL	LED LUMINAIRE – COBRA HEAD, 105 WATT (APPROX.), 12,700 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, WITH PE RECEPTACLE	EA	
33	AMERICAN ELECTRIC	ATB0-30BLED13-480-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 125 WATT (APPROX.), 14,800 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
34	AMERICAN ELECTRIC	ATB0-30BLED13-MVOLT-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 125 WATT (APPROX.), 14,800 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
35	AMERICAN ELECTRIC	ATB0-30BLED13-MVOLT-R3-20-NL-NR-PCLL	LED LUMINAIRE – COBRAHEAD, 125 WATT (APPROX.), 14,800 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, WITH PE RECEPTACLE, (FOR INSTALL IN COMMUTER PARKING LOTS)	EA	
36	AMERICAN ELECTRIC	ATB2-60BLEDE70-480-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 130 WATT (APPROX.), 18,200 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
37	AMERICAN ELECTRIC	ATB2-60BLEDE70-480-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 130 WATT (APPROX.), 17,700 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
38	AMERICAN ELECTRIC	ATB2-60BLEDE70-MVOLT-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 130 WATT (APPROX.), 18,200 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
39	AMERICAN ELECTRIC	ATB2-60BLEDE70-MVOLT-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 130 WATT (APPROX.), 17,700 LUMEN (APPROX.), 4000K, MULTI- VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
40	AMERICAN ELECTRIC	ATB2-60BLEDE70-MVOLT-R3-20-NL-PCLL	LED LUMINAIRE – COBRAHEAD, 130 WATT (APPROX.), 17,700 LUMEN (APPROX.), 4000K, MULTI- VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, WITH PE RECEPTACLE	EA	
41	AMERICAN ELECTRIC	ATB2-60BLEDE85-480-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 165 WATT(APPROX.), 21,400 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
42	AMERICAN ELECTRIC	ATB2-60BLEDE85-480-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 165 WATT (APPROX.), 21,400 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
43	AMERICAN ELECTRIC	ATB2-60BLEDE85- MVOLT-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 165 WATT (APPROX.), 21,400 LUMEN (APPROX.), 4000K, MULTI- VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
44	AMERICAN ELECTRIC	ATB2-60BLEDE85- MVOLT-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 165 (APPROX.) WATT, 21,400 LUMEN (APPROX.), 4000K, MULTI- VOLT, , 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
45	AMERICAN ELECTRIC	ATB2-60BLEDE10-480-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 204 WATT (APPROX.), 25,000 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
46	AMERICAN ELECTRIC	ATB2-60BLEDE10-480-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 204 WATT(APPROX.), 25,500 LUMEN (APPROX.), 4000K, 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
47	AMERICAN ELECTRIC	ATB2-60BLEDE10-MVOLT-R2-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 204 WATT (APPROX.), 25,000 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 2 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
48	AMERICAN ELECTRIC	ATB2-60BLEDE10-MVOLT-R3-20-NL-NR	LED LUMINAIRE – COBRAHEAD, 204 WATT (APPROX.), 25,500 LUMEN (APPROX.), 4000K, MULTI-VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 3 DISTRIBUTION, L70>100K HRS @25°C, NO PE RECEPTACLE	EA	
49	HOLOPHANE NO SUBSTITUTES	MGLEDM-P2-40K-480-FT-VH-GRSD-NL	ROADWAY LUMINAIRE – 125 WATT LED, 20,000 LUMEN (APPROX.), 480 VOLT, 20KV/10KA SURGE (FAIL OFF), FORWARD THROW, - (PEARL HARBOR MEMORIAL BRIDGE) – NO SUBSTITUTES	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
50	LUMEC	RFL-ORL-241W112LED-4K-G2-4-HVU-KAV3-API-NRC-SP2-GY3	LED LUMINAIRE – VERTICAL TENON MOUNT ROADWAY LUMINAIRE, 240 WATTS, 30,000 LUMEN (APPROX.), 480 VOLT, 20KV/10KA SURGE (FAIL OFF), TYPE 4 DIST.	EA	
51	HOLOPHANE	HMST400HP48A8	LUMINAIRE – HIGH MAST – 400 WATT HPS, 480 VOLT, ASYMMETRIC DISTRIBUTION, GLASS REFRACTOR WITH OPEN BOTTOM	EA	
52	HOLOPHANE	HMST400HP48L9	LUMINAIRE – HIGH MAST – 400 WATT HPS, 480 VOLT, LONG AND NARROW DISTRIBUTION, GLASS REFRACTOR WITH OPEN BOTTOM 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
53	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-AW-FD2	LUMINAIRE - LED HIGHMAST - 475 WATT, 64,740 LUMEN (APPROX.), AREA WIDE DISTRIBUTION, 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
54	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-N-FD2	LUMINAIRE - LED HIGHMAST - 475 WATT, 61,500 LUMEN (APPROX.), NARROW ASYMMETRIC DISTRIBUTION, 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
55	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-M-FD2	LUMINAIRE - LED HIGHMAST - 475 WATT, 61,460 LUMEN (APPROX.), MEDIUM ASYMMETRIC DISTRIBUTION, 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
56	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-LN-FD2	LUMINAIRE - LED HIGHMAST - 475 WATT, 66,800 LUMEN (APPROX.), LONG AND NARROW DISTRIBUTION, 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
57	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-F-FD2	LUMINAIRE - LED HIGHMAST - 475 WATT, 55,420 LUMEN (APPROX.), FORWARD THROW ASYMMETRIC DISTRIBUTION, 20KV/10KA SURGE, DOUBLE FUSIBLE DISCONNECT	EA	
58	HOLOPHANE	HMLED3-PK3-40K-HVOLT-G-AW	LUMINAIRE - LED HIGHMAST - 475 WATT, 66,740 LUMEN (APPROX.), AREA WIDE DISTRIBUTION	EA	
59	HOLOPHANE	HL2A400HP48G1	LUMINAIRE – INTERSTATE – 400 WATT HPS, 480 VOLT, KNUCKLE FITTER FOR TENON MOUNT	EA	
60	HOLOPHANE	W4100HP48SG	LUMINAIRE – UNDERBRIDGE WALL MOUNT – 100 WATT HPS, 480 VOLT	EA	
61	HOLOPHANE	W4100HPMASG	LUMINAIRE – UNDERBRIDGE WALL MOUNT – 100 WATT HPS, MULTI-VOLT	EA	
62	HOLOPHANE	W4150AHP48SG	LUMINAIRE – UNDERBRIDGE WALL MOUNT – 150 WATT HPS, 480 VOLT	EA	
63	HOLOPHANE	W4150AHPMASG	LUMINAIRE – UNDERBRIDGE WALL MOUNT – 150 WATT HPS, MULTI-VOLT	EA	
64	HOLOPHANE LITHONIA	W4GLED-10C-1000-40K-T3M-480-GYSDP TWHLED-10C-1000-40K-T3M-480-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 40 WATT (APPROX.), 3,375 LUMENS (APPROX.), 4000K, 480 VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	
65	HOLOPHANE LITHONIA	W4GLED-10C-1000-40K-T3M-MVOLT-GYSDP TWHLED-10C-1000-40K-T3M-MVOLT-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 40 WATT (APPROX.), 3,375 LUMENS (APPROX.), 4000K, MULTI-VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
66	HOLOPHANE LITHONIA	W4GLED-20C-1000-40K-T3M-480-GYSDP THWLED-20C-1000-40K-T3M-480-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 75 WATT (APPROX.), 7,000 LUMENS (APPROX.), 4000K, 480 VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	
67	HOLOPHANE LITHONIA	W4GLED-20C-1000-40K-T3M-MVOLT-GYSDP THWLED-20C-1000-40K-T3M-MVOLT-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 75 WATT (APPROX.), 7,000 LUMENS (APPROX.), 4000K, MULTI-VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	
68	HOLOPHANE LITHONIA	W4GLED-30C-1000-40K-T3M-480-GYSDP TWHLED-30C-1000-40K-T3M-480-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 104 WATT (APPROX.), 8,375 LUMENS (APPROX.), 4000K, 480 VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	
69	HOLOPHANE LITHONIA	W4GLED-30C-1000-40K-T3M-MVOLT-GYSDP TWHLED-30C-1000-40K-T3M-MVOLT-DNAXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, 104 WATT (APPROX.), 8,375 LUMENS (APPROX.), 4000K, MULTI-VOLT, TYPE 3 MEDIUM DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 2.5KV SURGE, L87>100K HRS @25°C	EA	
70	LITHONIA	CSXW LED-30C-700-40K-T4M-480-BBW-DDBXD	LED LUMINAIRE – UNDERBRIDGE WALL MOUNT, FULL- CUTOFF OPTICS, 70 WATT (APPROX.), 6,900 LUMEN (APPROX.), 4000K, 480V VOLT, TYPE 4 MEDIUM DISTRIBUTION	EA	
71	HOLOPHANE	RS2L100HP48TA21	LUMINAIRE – UNDERBRIDGE PENDANT – 100 WATT HPS, 480 VOLT, CLOSED GLASS BOTTOM	EA	
72	HOLOPHANE	RS2L100HPMTTA21	LUMINAIRE – UNDERBRIDGE PENDANT – 100 WATT HPS, MULTI-VOLT, CLOSED GLASS BOTTOM	EA	
73	HOLOPHANE	RS2L15AHP48TA21	LUMINAIRE – UNDERBRIDGE PENDANT – 150 WATT HPS, 480 VOLT, CLOSED GLASS BOTTOM	EA	
74	HOLOPHANE	PPSQL2-P60-40K-48-GL-T5W-STM-GYSDP	LED LUMINAIRE – UNDERBRIDGE PENDANT, 66 WATT (APPROX.), 7,100 LUMENS (APPROX.), 4000K, 480 VOLT, TYPE 5 WIDE DISTRIBUTION, 20KV/10KA SURGE, L70>100K HRS @25°C	EA	
75	HOLOPHANE	PPSQL2-P60-40K-AS-GL-T5W-STM-GYSDP	LED LUMINAIRE – UNDERBRIDGE PENDANT, 66 WATT (APPROX.), 7,100 LUMENS (APPROX.), 4000K, MULTI-VOLT, TYPE 5 WIDE DISTRIBUTION, 20KV/10KA SURGE, L70>100K HRS @25°C	EA	
76	HOLOPHANE	PPSQL2-P70-40K-48-GL-T5W-STM-GYSDP	LED LUMINAIRE – UNDERBRIDGE PENDANT, 80 WATT (APPROX.), 8,300 LUMENS (APPROX.), 4000K, 480 VOLT, TYPE 5 WIDE DISTRIBUTION, 20KV/10KA SURGE, L70>100K HRS @25°C	EA	
77	HOLOPHANE	PPSQL2-P70-40K-AS-GL-T5W-STM-GYSDP	LED LUMINAIRE – UNDERBRIDGE PENDANT, 80 WATT (APPROX.), 8,300 LUMENS (APPROX.), 4000K, MULTI-VOLT, TYPE 5 WIDE DISTRIBUTION, 20KV/10KA SURGE, L70>100K HRS @25°C	EA	
78	HOLOPHANE	PLED2-10L-4K-48-UN-NA-G-L1	LED LUMINAIRE – UNDERBRIDGE PENDANT, 100 WATT (APPROX.), 10,000 LUMENS (APPROX.), 480 VOLT, TYPE 1 LONG AND NARROW DISTRIBUTION WITH PRISMATIC GLASS REFRACTOR, 10KV/10KA SURGE, L85>100K HRS @25°C	EA	
79	HOLOPHANE	MW15AHPMTGF1	LUMINAIRE – TUNNEL WALL MOUNT – 150 WATT HPS, MULTI-VOLT, FUSED	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
80	HOLOPHANE	MW400HPMTGF1	LUMINAIRE – TUNNEL WALL MOUNT – 400 WATT HPS, MULTI-VOLT, FUSED	EA	
81	HOLOPHANE NO SUBSTITUTES	PD15AHPMTKW3GF1	LUMINAIRE – TUNNEL WALL MOUNT – 150 WATT HPS, MULTI-VOLT, FUSED – (I-84 PLATFORM LIGHTING) - (I-84 PLATFORM LIGHTING) - NO SUBSTITUTES	EA	
82	HOLOPHANE NO SUBSTITUTES	PF400HPMTKW3GPSF1	LUMINAIRE – TUNNEL WALL MOUNT – 400 WATT HPS, MULTI-VOLT, FUSED – (I-84 PLATFORM LIGHTING) - (I-84 PLATFORM LIGHTING) - NO SUBSTITUTES	EA	
83	HOLOPHANE NO SUBSTITUTES	TPF400HPMTKC6GPSF1-RFD100025	LUMINAIRE – TUNNEL CEILING MOUNT – 400 WATT HPS, MULTI-VOLT, FUSED, WITH COUNTER BEAM OPTICS – (I-84 PLATFORM LIGHTING) – NO SUBSTITUTES	EA	
84	HOLOPHANE	TNLEDMED-PK2-40K-MVOLT-UDP-DGRA-L-BM-F1	LED LUMINAIRE - TUNNEL WALL MOUNT, 70 WATT (APPROX.), 8,500 LUMENS (APPROX.), 4000K, MULTI-VOLT, PRISMATIC GLASS REFRACTOR, 20KV/10KA SURGE, L70>100K HRS @25°C, SINGLE FUSE	EA	
85	HOLOPHANE	TNLEDMED-PK4-40K-HVOLT-WCR-DGRA-L-TW	LED LUMINAIRE - TUNNEL WALL MOUNT, 125 WATT (APPROX.), 15,400 LUMENS (APPROX.), 480 VOLT, WALL MOUNT CROSS BEAM OPTICS WITH PRISMATIC GLASS REFRACTOR, 20KV/10KA SURGE, L70>100K HRS @25°C	EA	
86	HOLOPHANE	TNLEDMED-PK7-40K-MVOLT-UDP-DGRA-L-BM-F1	LED LUMINAIRE - TUNNEL WALL MOUNT, 200 WATT (APPROX.), 23,000 LUMENS (APPROX.), 4000K, MULTI-VOLT, PRISMATIC GLASS REFRACTOR, 20KV/10KA SURGE, L70>100K HRS @25°C, SINGLE FUSE	EA	
87	LUMEC	DMS50-110W64LED4K-T-LE2F-480-SMB-BRTX	LED LUMINAIRE – DECORATIVE, 105 WATTS, 11,250 LUMEN (APPROX.), 480 VOLT, TYPE 2 DIST., (FOR FOUNDERS BRIDGE)	EA	
88	SEALITE USA	SL-BR-G-360-AC	LED NAVIGATION LIGHT (PENDENT MOUNTED), 360° GREEN, 120 VOLT, 35 cd, PHOTOCELL OFF	EA	
89	SEALITE USA	SL-BR-R-180-AC	LED NAVIGATION LIGHT (PENDENT MOUNTED), 180° RED, 120 VOLT, 35 cd, PHOTOCELL OFF	EA	
90	SEALITE USA	SL-BR-R-180-DC (SOLAR)	LED NAVIGATION LIGHT (PIER MOUNTED), 180° RED, SOLAR POWERED FROM EXTERNAL BATTERY AND PANEL, 35 cd, PHOTOCELL OFF	EA	
91	MCDERMOTT LIGHT & SIGNAL SEALITE USA	9SOL-FM-RED SL70-180-R-16AH	LED NAVIGATION LIGHT (PIER MOUNTED), 180° RED, WITH INTEGRAL NiMH BATTERY, SOLAR PANEL, AND PHOTOCELL	EA	
92	LEDTRONICS	BBL5080102	LED LAMP – RED LIGHT EMITTING DIODE LAMP, 96 RED LEDS IN A CYLINDRICAL STACK OF 8 RINGS OF 12 LEDS EACH SEALED IN A WEATHERPROOF CLEAR POLYCARBONATE LENS, E26 SCREW BASE, 120 VOLT, 3.6 WATTS, 110 LUMENS	EA	

**EXHIBIT B
PRICE SCHEDULE**

CONTRACT NO: 20PSX0025

Rev. 10-30-19 Prev. Rev. 7/16/19

CONTRACTOR NAME:		
DELIVERY:	NET 30 DAYS ARO <input type="checkbox"/> yes <input type="checkbox"/> no (check a box)	PROMPT PAYMENT TERMS:

	MANUFACTURER	MANUFACTURER CATALOG NUMBER	INVENTORY ITEM DESCRIPTION	Unit of Measure	Price
93	LEDTRONICS	BBL5080302	LED LAMP – GREEN LIGHT EMITTING DIODE LAMP, 96 GREEN LEDS IN A CYLINDRICAL STACK OF 8 RINGS OF 12 LEDS EACH SEALED IN A WEATHERPROOF CLEAR POLYCARBONATE LENS, E26 SCREW BASE, 120 VOLT, 2.88 WATTS, 182 LUMENS	EA	