

CONTRACT SUPPLEMENT  
SP-37 - Rev. 11/14/19  
Prev. Rev. 10/24/19

Paul Greco  
Contract Specialist

860-713-5189  
Telephone Number

# STATE OF CONNECTICUT

DEPARTMENT OF ADMINISTRATIVE SERVICES

PROCUREMENT DIVISION

450 Columbus Boulevard, Hartford, CT 06103

CONTRACT AWARD NO.:

17PSX0120

Contract Award Date:

18 September 2017

Bid Due Date:

11 September 2017

SUPPLEMENT DATE:

11 December 2019

## CONTRACT AWARD SUPPLEMENT #5

**IMPORTANT: THIS IS NOT A PURCHASE ORDER. DO NOT PRODUCE OR SHIP WITHOUT AN AGENCY PURCHASE ORDER.**

DESCRIPTION: Motor Vehicle **Oils, Lubricants and Greases**

|  |  |   |   |
|--|--|---|---|
| FOR:<br><b>Department of Administrative Services, All Using State Agencies, and Political Subdivisions</b> |  | TERM OF CONTRACT:<br><b>November 1, 2017 through October 31, 2022</b> |   |
|  |  | AGENCY REQUISITION NUMBER: 4920                                       |   |
| CHANGE TO IN STATE (NON-SB)<br>CONTRACT VALUE  | CHANGE TO DAS-CERTIFIED SMALL<br>BUSINESS CONTRACT VALUE | CHANGE TO OUT OF STATE<br>CONTRACT VALUE                              | CHANGE TO TOTAL CONTRACT<br>AWARD VALUE |
|  |  |   | \$ Undetermined                         |

**NOTICE TO CONTRACTORS:** This notice is not an order to ship. Purchase Orders against contracts will be furnished by the using agency or agencies on whose behalf the contract is made. INVOICE SHALL BE RENDERED DIRECT TO THE ORDERING AGENCY.

**DISCLAIMER OF VALUE:** The total Contract Award amount stated is intended solely as an estimate, and does not constitute a representation of the actual value of the Contract.

**CASH DISCOUNTS:** Cash discounts, if any, shall be given SPECIAL ATTENTION, but such cash discount shall not be taken unless payment is made within the discount period.

**PRICE BASIS:** Unless otherwise noted, prices include delivery and transportation charges fully prepaid f.o.b. agency. No extra charge is to be made for packing or packages.

### PLEASE NOTE:

All terms and conditions not otherwise affected by this supplement remain unchanged and in full force and effect.

### CONTRACTOR INFORMATION:

REFER TO THE CONTRACT ON THE DAS PROCUREMENT WEB PAGE FOR THE MOST CURRENT CONTRACTOR INFORMATION. (<http://das.ct.gov/mp1.aspx?page=8>)

Company Name: **Dennison Lubricants**

Company Address: **111 Rhode Island Rd. Lakeville, MA 02347**

Tel. No.: **800-564-5142**

Contract Value: **Est. \$400,000.00**

Contact Person: **Brian Dennison**

Contact Person Address: **same**

Company E-mail Address and/or Company Web Site: **briand@denlube.com**

Remittance Address: **same**

Certification Type (SBE, MBE or None): **none**

Agrees to Supply Political Sub-Divisions: **Yes**

See Supplement Five Dennison Lubricants Exhibit B Price Schedule for revised pricing effective 12/2/2019.

DEPARTMENT OF ADMINISTRATIVE SERVICES

By: \_\_\_\_\_  
(Original Signature on Document in Procurement Files)

Name: **PAUL GRECO**

Title: Contract Specialist

Date: 12/02/2019

| 17PSX0120 Supplement 5 |  | Contractor - Dennison Lubricants AA |            |     | 12/2/2019      |                 |
|------------------------|--|-------------------------------------|------------|-----|----------------|-----------------|
| LINE ITEM              | Product Description  | Manufacturer                        | PART NO    | UOM | Contract Price | CM #            |
| 1                      | DIESEL ENGINE OIL SAE-15W-40- BULK DELIVERY - MUST MEET OR EXCEED PERFORMANCE REQUIREMENTS OF API SERVICE CAT DJ-4SL - CATERPILLAR ECF-3 - CUMMINS CES 20086 - DETROIT DIESEL DFS93K222 SPECS AND INTERNATIONAL (NAVISTAR) DIESEL ENGINE WARRANTY REQUIREMENTS | GULF SUPER DUTY 15W040              | 002-331307 | GA  | 5.48           | CM_2157_9002633 |
| 2                      | DIESEL ENGINE OIL SAE-15W-40 - 55 GALLON DRUM - MUST MEET OR EXCEED PERFORMANCE REQUIREMENTS OF API SERVICE CAT DJ-4SL CATERPILLAR ECF-3 CUMMINS CES 20086 DETROIT DIESEL DFS93K222 SPECS AND INTERNATIONAL (NAVISTAR) DIESEL ENGINE WARRANTY REQUIREMENTS     | GULF SUPER DUTY 15W040              | 331307D    | DR  | 328.60         | CM_2157_9002578 |
| 3                      | ENGINE OIL SAE 5W-30 SYNTHETIC BLEND - BULK DELIVERY - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN ILSAC GF-5 GM 6094M & FORD WSS-M2C946-A SPECS   | GULF SYN-BLEND 5W30                 | 002-330133 | GA  | 4.57           | CM_2157_9002563 |
| 4                      | ENGINE OIL SAE 5W-30 SYNTHETIC BLEND - 55 GALLON DRUM - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN ILSAC GF-5 GM 6094M & FORD WSS-M2C946-A SPECS  | GULF SYN-BLEND 5W30                 | 330133D    | DR  | 274.60         | CM_2157_9002571 |
| 5                      | ENGINE OIL SAE 5W-30 SYNTHETIC BLEND - 12 QUARTS PER CASE - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN ILSAC GF-5 GM 6094M & FORD WSS-M2C946-A SPECS  | GULF SYN-BLEND 5W30                 | 330133     | CA  | 21.20          | CM_2157_9002570 |
| 6                      | ENGINE OIL SAE 5W-30 FULL SYNTHETIC - BULK DELIVERY - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN ILSAC GF-5 DEXOS 1 & FORD WWSS-M2C946-A SPECS  | GULF FULL SYN DEXOS 5W30            | 002-330200 | GA  | 6.12           | CM_2157_9002623 |
| 7                      | ENGINE OIL SAE 5W-30 FULL SYNTHETIC - 55 GALLON DRUM MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN ILSAC GF-5 DEXOS 1 & FORD WSS-M2C946-A SPECIFICATIONS   | GULF FULL SYN DEXOS 5W30            | 330200D    | DR  | 359.40         | CM_2157_9002573 |
| 8                      | ENGINE OIL SAE 5W-30 FULL SYNTHETIC -12 QUARTS PER CASE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5, DEXOS 1 AND FORD WSS-M2C946-A SPECIFICATIONS  | GULF FULL SYN DEXOS 5W30            | 330200     | CA  | 30.44          | CM_2157_9002625 |
| 9                      | ENGINE OIL SAE 0W-20 FULL SYNTHETIC - BULK DELIVERY MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5 & DEXOS 1 SPECIFICATIONS   | GULLF FULL SYN DEXOS 0W20           | 002-330222 | GA  | 5.96           | CM_2157_9002565 |

|    |   |                          |           |         |               |                 |
|----|---|--------------------------|-----------|---------|---------------|-----------------|
| 10 | ENGINE OIL SAE 0W-20 FULL SYNTHETIC - 55 GALLON DRUM MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5 & DEXOS 1 SPECIFICATIONS   | GULF FULL SYN DEXOS 0W20 | 330222D   | DR      | <b>349.90</b> | CM_2157_9002575 |
| 11 | ENGINE OIL SAE 0W-20 FULL SYNTHETIC - 12 QUARTS PER CASE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5 & DEXOS 1 SPECIFICATIONS   | GULF FULL SYN DEXOS 0W20 | 330222    | CA      | <b>30.44</b>  | CM_2157_9002619 |
| 12 | ENGINE OIL SAE 30 - 55 GALLON DRUM MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION CF  | GULF SUPER DUTY 30W      | 331303D   | DR      | <b>393.10</b> | CM_2157_9002576 |
| 13 | ENGINE OIL SAE 30 - 12 QUARTS PER CASE - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION   | SHELL ROTELLA T1 30W     | 550019903 | CA      | <b>40.33</b>  | CM_2157_9002697 |
| 14 | ENGINE OIL SAE 40 - 55 GALLON DRUM MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION CF  | GULF SUPER DUTY 40W      | 331304D   | DR      | <b>402.81</b> | CM_2157_9002577 |
| 15 | ENGINE OIL SAE 40 - 12 QUARTS PER CASE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION CF  | SHELL ROTELLA T1 40W     | 550019904 | CA      | <b>40.33</b>  | CM_2157_9002595 |
| 16 | AUTOMATIC TRANSMISSION FLUID 6 QUARTS PER CASE - MULTI-PURPOSE - MULTI-VEHICLE HIGH-VISCOSITY MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF ALLISON TRANSMISSION C-4 FORD MERCON & MERCON V - GM DEXRON - II AND DEXRON -III SPECIFICATIONS | OILZUM SYN MV ATF        | OZ01790   | 6 qt CA | <b>21.58</b>  | CM_2157_9002604 |
| 17 | AUTOMATIC TRANSMISSION FLUID - 5 GALLON PAIL MULTI PURPOSE MULTI-VEHICLE HIGH VISCOSITY MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF ALLISON TRANSMISSION C-4 FORD MERCON & MERCON V GM DEXRON - II AND DEXRON -III SPECIFICATIONS         | OILZUM SYN MV ATF        | OZSYNATFP | PA      | <b>45.54</b>  | CM_2157_9002605 |
| 18 | AUTOMATIC TRANSMISSION FLUID - 55 GALLON DRUM SYNTHETIC LV MULTI-VEHICLE LOW VISCOSITY ATF MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF FORD MERCON LV XT-10-QLV AND GM DEXRON-VI SPECS  | GULF SYN MV DEX VI       | 330030D   | DR      | <b>554.86</b> | CM_2157_9002569 |
| 19 | AUTOMATIC TRANSMISSION FLUID - 12 QUARTS PER CASE - SYNTHETIC LV MULTI-VEHICLE LOW-VISCOSITY ATF MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF FORD MERCON LV XT-10-QLV AND GM DEXRON-VI SPECIFICATIONS                                     | GULF SYN MV DEX VI       | 330024    | CA      | <b>48.40</b>  | CM_2157_9002568 |
| 20 | AUTOMATIC TRANSMISSION FLUID - 55 GALLON DRUM ATF PLUS 4 F/ MOPAR SPECIFICALLY DESIGNED FOR CHRYSLER VEHICLES EQUIPPED WITH AUTOMATIC TRANSMISSIONS MUST MEET OR EXCEED CHRYSLER MATERIAL STANDARDS MS-9602 ATF PLUS 4 SPECIFICATIONS             | SHELL ATF 134            | 55002374  | DR      | <b>942.75</b> | CM_2157_9002596 |

|    |   |                          |           |    |          |                 |
|----|---|--------------------------|-----------|----|----------|-----------------|
| 21 | AUTOMATIC TRANSMISSION FLUID - 12 QUARTS PER CASE ATF PLUS 4 F/ MOPAR SPECIFICALLY DESIGNED FOR CHRYSLER VEHICLES EQUIPPED WITH AUTOMATIC TRANSMISSIONS MUST MEET OR EXCEED CHRYSLER MATERIAL STANDARDS MS-9602 ATF PLUS 4 SPECIFICATIONS | SHELL ATF 134            | 5080660   | CA | 58.36    | CM_2157_9002593 |
| 22 | AUTOMATIC TRANSMISSION FLUID - 55 GALLON DRUM ALLISON TES 295 MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF ALLISON TRANSMISSION TES 295 SPECIFICATIONS   | SHELL SPIRAX S6 A295     | 550032968 | DR | 1310.70  | CM_2157_9002598 |
| 23 | AUTOMATIC TRANSMISSION FLUID - 5 GALLON PAIL ALLISON TES 295 - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF ALLISON TRANSMISSION TES 295 SPECIFICATIONS  | SHELL SPIRAX S6 A295     | 550032647 | PA | 155.69   | CM_2157_9002630 |
| 24 | MANUAL TRANSMISSION - 5 GALLON PAIL - SAE 50 SYNTHETIC GEAR LUBE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J2360 AND EATON LUBRICANT SPECIFICATION PS-386                              | GULF SYN TRANS 50W       | 337205P   | PA | 89.82    | CM_2157_9002588 |
| 25 | MANUAL TRANSMISSION - 12 QUARTS PER CASE - SAE 50 SYNTHETIC GEAR LUBE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J2360 AND EATON LUBRICANT SPECIFICATION PS-386                      |                          |           | CA | No Award |                 |
| 26 | GEAR LUBE - SAE 75W-90 SYNTHETIC GEAR LUBE - 55 GALLON DRUM - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J2360, DANA EATON SHAES-256 AND MERITOR O-76N SPECS                         | GULF SYN 75W90           | 337201D   | DR | 811.94   | CM_2157_9002627 |
| 27 | GEAR LUBE - SAE 75W-90 SYNTHETIC GEAR LUBE - 5 GALLON PAIL MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J2360, DANA- EATON SHAES-256 AND MERITOR O-76N SPECS                           | GULF SYN 75W90           | 337201P   | PA | 82.69    | CM_2157_9002585 |
| 28 | GEAR LUBE - SAE 75W-90 SYNTHETIC GEAR LUBE - 12 QUARTS PER CASE - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J2360, DANA- EATON SHAES-256 AND MERITOR O-76N SPECS                    | PENNZOIL PLAT SYN 75W90  | 550042045 | CA | 135.60   | CM_2157_9002599 |
| 29 | GEAR LUBE - SAE 75W-140 SYNTHETIC GEAR LUBE - 35 GALLON DRUM - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J306 AND FORD WSL-M2C192-A SPECS   | GULF SYN 75W140          | 337203P   | DR | 1369.58  | CM_2157_9002690 |
| 30 | GEAR LUBE - SAE 75W-140 SYNTHETIC GEAR LUBE - 12 QUARTS PER CASE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION GL-5 & MT-1, SAE J306 AND FORD WSL-M2C192-A SPECS   | PENNZOIL PLAT SYN 75W140 | 550042070 | CA | 162.95   | CM_2157_9002600 |

|    |   |                   |            |    |               |                 |
|----|---|-------------------|------------|----|---------------|-----------------|
| 31 | HYDRAULIC OIL - ISO GRADE 32 ALL SEASON AW - BULK DELIVERY - MUST CONTAIN AN ANTIWEAR ADDITIVE CORROSION OXIDATION AND FOAM INHIBITORS MUST MEET OR EXCEED ASTM THERMAL OXIDATION TEST D-943 (3,000 HOUR MINIMUM), EATON VICKERS I-286-S & M-2950-S, ISO 11158 HM AND PARKER DENISON HF-0 SPECIFICATIONS MINIMUM VISCOSITY INDEX OF 95  | GULF HARMONY AW32 | 002-334227 | GA | <b>3.94</b>   | CM_2157_9002567 |
| 32 | HYDRAULIC OIL - ISO GRADE 32 ALL SEASON AW - 55 GALLON DRUM - MUST CONTAIN AN ANTI-WEAR ADDITIVE CORROSION OXIDATION AND FOAM INHIBITORS MUST MEET OR EXCEED ASTM THERMAL OXIDATION TEST D-943 (3,000 HR. MINIMUM), EATON VICKERS I-286-S & M-2950-S, ISO 11158 HM AND PARKER DENISON HF-0 SPECIFICATIONS MINIMUM VISCOSITY INDEX OF 95 | GULF HARMONY AW32 | 334227D    | DR | <b>239.54</b> | CM_2157_9002583 |
| 33 | HYDRAULIC OIL - ISO GRADE 32 ALL SEASON AW - 5 GALLON PAIL MUST CONTAIN AN ANTI-WEAR ADDITIVE CORROSION OXIDATION AND FOAM INHIBITORS - MUST MEET OR EXCEED ASTM THERMAL OXIDATION TEST D-943 (3,000 HR MINIMUM), EATON-VICKERS I-286-S & M-2950-S, ISO 11158 HM AND PARKER DENISON HF-0 SPECIFICATIONS MINIMUM VISCOSITY INDEX OF 95   | GULF HARMONY AW32 | 334227P    | PA | <b>24.86</b>  | CM_2157_9002584 |
| 34 | UNIVERSAL TRACTOR HYDRAULIC OIL - 55 GALLON DRUM SAE 10W MUST CONTAIN AN ANTI-WEAR ADDITIVE CORROSION OXIDATION AND FOAM INHIBITORS MUST MEET OR EXCEED CASE NH MAT 3505 CATERPILLAR TO-2 & JOHN DEERE J-20-C REQUIREMENTS MINIMUM VISCOSITY INDEX OF 140   | GULF UTF          | 331953D    | DR | <b>324.35</b> | CM_2157_9002581 |
| 35 | UNIVERSAL TRACTOR HYDRAULIC OIL - 5 GALLON PAIL - SAE 10W MUST CONTAIN AN ANTI-WEAR ADDITIVE CORROSION OXIDATION AND FOAM INHIBITORS MUST MEET OR EXCEED CASE NH MAT 3505 CATERPILLAR TO-2 & JOHN DEERE J-20-C REQUIREMENTS MINIMUM VISCOSITY INDEX OF 140  | GULF UTF          | 331953P    | PA | <b>33.65</b>  | CM_2157_9002582 |
| 36 | TRANS/DRIVE TRAIN FLUID - 55 GALLON DRUM - SAE 30W F/ OFF-HIGHWAY EQ MUST CONTAIN ANTI-WEAR AND FRICTION ADDITIVES CORROSION OXIDATION AND FOAM INHIBITORS - MUST MEET OR EXCEED CATERPILLAR TO-4 PERFORMANCE REQUIREMENTS MINIMUM VISCOSITY INDEX OF 95  | GULF TO-4 30W     | 331930D    | DR | <b>409.27</b> | CM_2157_9002579 |
| 37 | TRANS/DRIVE TRAIN FLUID - 5 GALLON PAIL SAE 30W F/ OFF-HIGHWAY EQ MUST CONTAIN ANTI-WEAR AND FRICTION ADDITIVES CORROSION OXIDATION AND FOAM INHIBITORS - MUST MEET OR EXCEED CATERPILLAR TO-4 PERFORMANCE REQUIREMENTS MINIMUM VISCOSITY INDEX OF 95   | GULF TO-4 30W     | 331930P    | PA | <b>42.30</b>  | CM_2157_9002580 |

|    |   |                   |             |               |                 |                 |
|----|---|-------------------|-------------|---------------|-----------------|-----------------|
| 38 | GREASE - 55 GALLON DRUM - NLGI #2 SAE MULTI-PURPOSE EP LITHIUM COMPLEX WATER RESISTANT CONTAINING MOLYBDENUM DISULFIDE AND ANTI-WEAR ADDITIVES DESIGNED FOR HIGH TEMPERATURE AND EXTREME PRESSURE MUST MEET OR EXCEED NLGI PERFORMANCE CLASSIFICATION GC-LB         | Gulf Flex 3%Moly  | 343013d     | DR            | <b>821.40</b>   | CM_2157_9002590 |
| 39 | GREASE - 10 CARTRIDGES PER CASE NLGI #2 SAE MULTI-PURPOSE EP - LITHIUM COMPLEX WATER RESISTANT CONTAINING MOLYBDENUM DISULFIDE AND ANTI-WEAR ADDITIVES DESIGNED FOR HIGH TEMPERATURE AND EXTREME PRESSURE MUST MEET OR EXCEED NLGI PERFORMANCE CLASSIFICATION GC LB | Gulf Flex 3%Moly  | 343013      | CA            | <b>24.45</b>    | CM_2157_9002626 |
| 40 | GREASE - SYNTHETIC 10 CARTRIDGES PER CASE NLGI #2 SAE EXTREME TEMPERATURE LITHIUM BASED WITH MOLYBDENUM DISULFIED DESIGNED FOR EXTREME TEMPERATURES AND PRESSURES MUST MEET OR EXCEED NLGI PERFORMANCE CLASSIFICATION GC LB   |                   |             | CA            | <b>No Award</b> |                 |
| 41 | GREASE - 5 GALLON PAIL NGLI #00 F/ AUTOMATED GREASE SYSTEMS - SEMI FLUID LITHIUM BASED WITH ANTI-WEAR AND CORROSION ADDITIVES DESIGNED FOR EXTREME PRESSURE AND LOW TEMPERATURE DELIVERY MUST MEET OR EXCEED NLGI PERFORMANCE LEVEL GP 00K-20                       | Gulf Crown 00     | 343304      | PA            | <b>73.37</b>    | CM_2157_9002592 |
| 42 | GREASE - 5 GALLON PAIL NGLI #000 F/ CONVEYER AND MOWER GEAR BOXES ANHYROUS CALCIUM MILD-EXTREME PRESSURE WATER REPELLANT SEMI-FLUID LUBRICANT SUCH AS LUBRIPLATE #5555  | Gulf Crown Ep 000 | 343303      | PA            | <b>73.37</b>    | CM_2157_9002591 |
| 43 | DEF DIESEL EXHAUST FLUID - BULK DELIVERY - MUST MEET THE API GERMAN INSTITUTE OF STANDARDIZATION DIN70700, ISO-22241-1 AND AUS - 32 SPECIFICATIONS DEF SHALL BE MANUFACTURED FROM 32.5% A HIGH PURITY SYNTHETIC UREA AND 67.5% DEIONIZED WATER                      | OILZUM DEF        | DEFBULK     | GA            | <b>1.29</b>     | CM_2157_9002602 |
| 44 | DEF - DIESEL EXHAUST FLUID - 55 GALLON DRUM - MUST MEET THE API GERMAN INSTITUTE OF STANDARDIZATION DIN70700, ISO-22241-1 AND AUS - 32 SPECIFICATIONS DEF SHALL BE MANUFACTURED FROM 32.5% A HIGH PURITY SYNTHETIC UREA AND 67.5% DEIONIZED WATER                   | OILZUM DEF        | 756368-OPEN | DR            | <b>89.90</b>    | CM_2157_9002601 |
| 45 | DEF - DIESEL EXHAUST FLUID - 2.5 GALLON CONTAINER - MUST MEET THE API GERMAN INSTITUTE OF STANDARDIZATION DIN70700, ISO-22241-1 AND AUS - 32 SPECIFICATIONS - DEF SHALL BE MANUFACTURED FROM 32.5% A HIGH PURITY SYNTHETIC UREA AND 67.5% DEIONIZED WATER           | OILZUM DEF        | OZ00250     | 2-2.5gl<br>CA | <b>11.98</b>    | CM_2157_9002603 |

|    |   |                      |            |    |               |                 |
|----|---|----------------------|------------|----|---------------|-----------------|
| 46 | ENGINE OIL SAE 5W-20 SYNTHETIC BLEND - BULK DELIVERY - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5, & FORD WSS-M2C945-A SPECIFICATIONS  | GULFPRIDE 5W20       | 002-330220 | GA | <b>4.57</b>   | CM_2157_9004093 |
| 47 | ENGINE OIL SAE 5W-20 SYNTHETIC BLEND - 55 GALLON DRUM - MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5, & FORD WSS-M2C945-A SPECIFICATIONS   | GULFPRIDE 5W20       | 330220D    | DR | <b>274.60</b> | CM_2157_9004104 |
| 48 | ENGINE OIL SAE 5W-20 SYNTHETIC BLEND - 12 QUARTS PER CASE MUST MEET OR EXCEED THE PERFORMANCE REQUIREMENTS OF API SERVICE CLASSIFICATION SN, ILSAC GF-5, & FORD WSS-M2C945-A SPECIFICATIONS   | GULFPRIDE 5W20       | 330220     | CA | <b>21.20</b>  | CM_2157_9004103 |
| 49 | Diesel Fuel Cetane Boost and anti-gelling agent 2/2.5 gallon case treatment ration 1-:1500  | Power Service        | 1050-02    | CA | <b>134.90</b> | CM_2157_4999908 |
| 38 | GREASE - 55 GALLON DRUM - NLGI #2 SAE MULTI-PURPOSE EP LITHIUM COMPLEX WATER RESISTANT CONTAINING MOLYBDENUM DISULFIDE AND ANTI-WEAR ADDITIVES DESIGNED FOR HIGH TEMPERATURE AND EXTREME PRESSURE MUST MEET OR EXCEED NLGI PERFORMANCE CLASSIFICATION GC-LB | Gulf Flex 3%Moly KEG | 343013K    | DR | <b>304.30</b> | CM_2157_        |